



SEMANGAT
IMPIAN

IMPIAN **X**

ADVENTURE EVERYWHERE

CRF
250 RALLY





DOHC 4V Single-Cylinder Engine

Instant delivery is provided by the 250cc engine with 18.3kW @ 9,000rpm and 21.9Nm of torque @ 6,500rpm.



Improved Suspension Settings

The upper suspension is now a bearing type with optimized rear damping, and the front suspension damping force is increased for a more stable and comfortable ride on or off-road.



Long Travel Suspension

The aggressive headlight design now features an even brighter LED light for optimum visibility and an even bigger presence on the road. LED indicators clearly signal your movements to other road users and pedestrians.



Lightweight Chassis

The lightweight steel semi-double cradle frame and aluminium swingarm ensure easy handling in all conditions, while the forged aluminium bottom yoke enhances stability and comfort.



Comprehensive Digital Dash

Easy-to-read information is laid out clearly and features a speedometer, rev-counter, fuel gauge and clock, and now also a gear position indicator.



Assist & Slipper Clutch

The Assist & Slipper Clutch smooths upshifts, reduces rear wheel 'hop' during hard braking and downshifts, providing extra control in traffic and essential support on tough off-road terrain.

CRF 250 RALLY



EXTREME RED

SPECIFICATIONS

ENGINE AND FUEL SYSTEM

Engine Type	Single Cylinder, Liquid Cooled, DOHC 4-Stroke 4 Valve
Displacement	250 cm ³
Bore x Stroke	76.0 mm x 55.0 mm
Compression Ratio	10.7 : 1
Max. Power	18.3 kW @ 9,000 rpm
Max. Torque	21.9 N.m @ 6,500 rpm
Engine Oil Capacity	1.75 l
Carburation	PGM-FI (Programmed Fuel Injection)

TRANSMISSION

Clutch Type	Manual Clutch Wet Multiplate Type with Assist & Slipper Clutch
Transmission Type	Constant Mesh, 6 Speeds

DIMENSION AND WEIGHT

Dimensions (L x W x H)	2,229 mm x 920 mm x 1,419 mm
Wheelbase	1,453 mm
Seat Height	893 mm
Ground Clearance	277 mm
Kerb Weight	153 kg
Fuel Tank Capacity	12.8 l

SUSPENSION

Suspension Type	Front: Showa 43mm Telescopic Upsidedown
	Rear: Showa Prolink

WHEELS AND BRAKE

Tyres	Front: 80/100 - 21M/C (51P)
	Rear: 120/80 - 18M/C (62P)
Brakes Type	Front: 296 mm Floating Wave Disc with 2-Piston Calliper, ABS
	Rear: 220 mm Hydraulic Single Disc with 1-Piston Calliper, ABS Rear Cancel Function

COLOUR VARIANT



EXTREME RED

Boon Siew Honda Sdn. Bhd. (676896-A)

721, Persiaran Cassia Selatan 1, Kawasan Perindustrian Batu Kawan, 14100 Simpang Ampat, Pulau Pinang.

HQ 04 506 3333 KL 03 6259 3516 / 03 6259 3517

JOHOR 07 244 8877 / 07 244 7557 TERENGGANU 09 624 0767 / 09 624 0746

All specifications are provisional and subject to change without notice.

- Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tyre pressure, installation of accessories, cargo, rider and passenger weight, and other factors.

- Colours and photos may vary from the actual product. These models come with a 2 year or 20,000km manufacturing warranty (whichever comes first).

Toll Free Line
1800 883993

Monday – Friday (9am – 5pm)

Close on public holidays

www.hondabigbike.com.my

Honda Motorcycle Malaysia

[hondamotorcycle.my](https://www.instagram.com/hondamotorcycle.my)

012-499 3991

AUTHORISED DEALER STAMP